

Bibliographic data: JP 11503637 (T)

RELOADABLE AUTO-INJECTOR

Publication date: 1999-03-30

Inventor(s):

Applicant(s): Classification:

- international: A61M5/20; A61M5/32; (IPC1-7): A61M5/20

- European: A61M5/200

Application number: JP19960531462T 19960417

Priority number(s): WO1996EP01603 19960417; FR19950004579 19950418

WO 9632974 (A1)
 US 6099503 (A)

Also published as: • FR 2733186 (A1)
• EP 0825883 (A1)

EP 0825883 (B1)
 more

Abstract not available for JP 11593637 (T) Abstract of corresponding document: WO 9632974 (A1)

A relocatable auto-injector including a housing portion (1, 101) for holding a syringe (3), and a ouver portion (2, 102). The auto-injector incorporates a device for automatically injecting the substance oroitation of the syringe Sald injection device comprises. a pumper (21) with an upper portion (21b) and a lower portion (21c), withol lower portion (21c) engages the syringe pumper, within said pumper (21) is in-unable by an actuating permy (22) between a prime position and apposition, said spring (22) hearing compressed in said primed position and inggering means (19) involvably involution between a position, said spring (22) hearing compressed in said primed position and actualing premiser. Said sub-injector of them and triggering means (19) heavy leaders from the backing position by an actualing members. Said sub-injector drafter comprises creams for reporting the subconsitiol rejector device, which reporting means are arranged to be actuated by the opening and/or chessing of said covers portions (2, 102) of the sub-injector.

Last updated: 26.04.2011 Worldwide Database 5,7.22: 93p